



I D E A L  
P A C K A G I N G S E R V I C E S

## **CHALI**® Strapping Systems

# JN-740 Series

### Semi-Automatic Strapping Machine

- Extra Safe
- Easy to Use and Maintain
- Heavy-Duty Capacity





## JN-600



## JN-700



- Designed for easy operation.
- Energy saving mode activates within 15 seconds of non-use and allows for instant operation.
- Lift type top cover allows convenient maintenance.
- External adjustable tension knob provides simple operation (optional).
- Easier changeover of straps suitable for 6~15mm strap width through strap guides.
- Internal power of DC 24V eliminates shock and prolongs machine life.
- Optional installation for different needs:
  1. Exchange of brake wheels available.
  2. 730~830mm height adjustable.
- Stainless steel frame is available for strapping humid products.

- Instant heating in only 20 seconds.
- One touch machine operation.
- Energy saving mode activates within 15 seconds of non-use and allows for instant operation.
- Simple adjustment of strap guides allow for strap width setting of 6mm to 15mm
- All electric parts installed on independent circuit boards.
- All electric controls utilize DC 24V to ensure safety.

Specifications:	JN-600	JN-700
Strap Cycle Speed	1.5 sec./ cycle	1.5 sec./ cycle
Tension Strength	65kgs /Max.	65kgs /Max.
Table Height	730mm	730mm
Strap Width	6~15mm	6~15mm
Sealing Method	Heat Sealing	Heat Sealing
Min. Package Size	60mm	60mm
Power Supply	110/220V 50/60Hz single phase	110/220V 50/60Hz single phase
Dimensions	895W x 570D x 730H mm	895W x 570D x 730H mm
Machine Weight	84kgs	92.5kgs
Gross Weight	101kgs	107kgs



## JN-740



## JN-740DH



- Instant heating in 20 seconds
- Economical design of control switch, independent PCB controls feeding, tensioning and heating.
- External adjustable tension knob provides simple operation (optional).
- Energy saving mode activates within 15 seconds of non-use and allows for instant operation.
- Innovative die-cast seal blade eliminates blade distortion, short circuiting and rapid aging that are common in many conventional strapping machines.
- Easier changeover of straps suitable for 6~15mm strap width through strap guide.
- Stainless steel frame is available for strapping humid products.

- Front door opening design makes loading and unloading dispenser more convenient.
- Instant heating in 20 seconds.
- Economical design of control switch, independent PCB controls feeding, tensioning and heating.
- External adjustable tension knob provides simple operation (optional).
- Energy saving mode activates within 15 seconds of non-use and allows for instant operation.
- Innovative die-cast seal blade eliminates blade distortion, short circuiting and rapid aging that are common in many conventional strapping machines.
- Easier changeover of straps suitable for 6~15mm strap width through strap guide.

### Specifications:

	JN-740	JN-740DH
Strap Cycle Speed	1.5 sec./ cycle	1.5 sec./ cycle
Tension Strength	15~60kgs	15~60kgs
Table Height	735mm	735mm
Strap Width	6~15mm	6~15mm
Sealing Method	Heat Sealing	Heat Sealing
Power Supply	110/220V 50/60Hz single phase	110/220V 50/60Hz single phase
Dimensions	895W x 570D x 735H mm	895W x 570D x 735H mm
Machine Weight	92.5kgs	97.5kgs
Gross Weight	107kgs	113kgs



# JN-7mini-B

# JN-600VS



- Suitable for light tension packaging in 6~15mm strap width.
- Energy saving mode activates within 15 seconds of non-use and allows for instant operation.
- Lift type top cover allows for convenient maintenance.
- Easy external adjustable tension knob from 15~45kgs.

- Internal power of DC 24V eliminates shock and prolongs machine life.
- Vertical side-seal head to minimizes dust, water or any contamination in the machine.
- Adjustable 20 step table height from 450~850mm, increases variety of package sizes and eliminates the need for tools.
- Use of changeable circuit board provides easy replacement and side-seal head ensures safety, easy maintenance.
- Optional installation for different needs:
  1. Use of stainless steel rollers to forward and reverse strap feed.
  2. Enlarged working table.
  3. Stainless steel castors instead of standard.
  4. Installation of internal lamp to keep cabinet dry.

Specifications:	JN-7mini-B	JN-600VS
Strap Cycle Speed	1.5 sec./ cycle	1.5 sec./ cycle
Tension Strength	15~45kgs	65kgs
Table Height	790mm	450~850mm
Strap Width	6,9,12,15mm	6~15mm
Sealing Method	Heat Sealed	Heat Sealing
Power Supply	110/220V 50/60Hz single phase	110/220V 50/60Hz single phase
Dimensions	630W x 420D x 790H mm	675W x 1045D x 1720H mm
Machine Weight	72kgs	122kgs
Gross Weight	90kgs	147kgs